

Vision E - S Plus

The satellite unit for Vision vending machines, Vision E-S Plus has a big elevator for product delivery allowing to place on sale big size products. Bread and dairy products, tools, big coffee bags, electronic gadgets, washing powder… the product delivery system of Vision machines, adjustable to any package shape, combined to this new delivery elevator for big products, it occupies the whole cabinet width, opens a new world of possibilities for products which previously didn't have a place on the vending channel, remarkable is as well the possibility to include a cooling unit and this way maintain on perfect conditions refrigerated products.



Technical characteristics

- Programmable temperature from 0,5 °C to 12° C
- Capacity of up to 8 fully adjustable trays and up to 10 channels each.
- FIFO system used to deliver products.
- Vend detection by photocells.
- Leds lightening system with on-off programming.
- Transparent area of 1169 x 714 mm.
- Auto - self diagnostic control system.
- Health timer that inhibits vends of out - of -date products.
- Flexible configuration. The easyFlex system allows the fast modification of the width and depth of the channel. No additional spare parts are needed to create a new configuration
- Programmable torque and speed of the motors.
- Power Supply: 220-240 VAC (Optional 110 V.)
- Maximum consumption 650w

Dimensions and weight

- Dimensions: 1825 x 800 x 975 mm (If the machines has a cooling unit the depth will be 1010mm)
- Weight: 325 Kg.

Structure

- Robust construction with an anti-corrosive and antioxidation coating material
- Security lock with 3 locking points
- Injected foam on all the cabinet, assures the best refrigeration using lower power consumption by the cooling unit.

Cash-credit management

- On the main vending machine, models Vision or Coffeemar

Programming and management

- On the main vending machine, models Vision or Coffeemar.

Options

- With or without cooling unit.



